




0201 Microscopic Footprint, Maximum Impact

Product Features

- Ultra-compact 0201 footprint SMD LED
- 0.65 x 0.35 x 0.20mm (LxWxH)
- Low Power consumption with exceptional intensity output
- Compatible with automatic placement equipment
- Moisture Sensitivity level: 2
- RoHS Compliant

Applications

- Backlighting
- Status indicators
- Enterprise solutions
- Disposable and wearable healthcare devices
- Robotic and automation systems



PRODUCT SPECIFICATION

Product Photos	Part Number	I _F (mA)	λD (nm)	lv (mcd)		Viewing
				Min.	Тур.	Angle
0.20 mm 0.35 mm 0.65 mm	APG0201VWF-A1-5MAV	5	☐ X=0.31 Y=0.31	180	320	140°
	APG0201VBC/A-5MAV	5	468	30	60	140°
	APG0201ZGC-5MAV	5	525	180	280	140°
	APG0201CGC-TT	10	<u> </u>	6	15	140°
	APG0201SYC-TT	10	589	10	30	140°
	APG0201SEC-TT	10	605	20	50	140°
	APG0201SEC-E-TT	10	624	15	40	140°
	APG0201SURC-TT	10	631	10	35	140°

OTHER COMPACT OPTIONS



