



## Single-digit RA Display LED

## No Mounting Adapter Needed

## **Product Features**

- 0.32 inch digit height
- Excellent character appearance
- High light output
- Mechanically rugged
- Easy mounting on P.C. board or sockets
- Black face, white segment
- RoHS compliant

## **Applications**

- Home and smart appliances
- Display time and digital combination
- Industrial and instrumental applications
- Numeric status

Part Number	Color	Wavelength	lv (mcd)		lF	Dimensions	
			Min.	Тур.	(mA)	Dimensions	
SA32-61QBWB-2BCB	•	465nm	5600	13000	10	7.8(0.307) 4(0.15z) 10 10 10 10 10 10 10 10 10 10	
SA32-61ZGKWB-2BCB	•	525nm	52000	111000	10	3.5(0,138) (9,10,10) (1,0,10)	
SA32-61LZGKWB-2BCB	•	525nm	21000	38000	2	0.42(0.017) Recommended PCB Layout  2.54x4=10.16(0.4)  1.2.7(0.5) 3 o o 8 2.54x4=10.16(0.4)   5.08(0.2)	
SA32-61GWB-2BCB	•	568nm	2200	5000	10	2 0 9 2.54(0.1) 9 7 7 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9	



